

Nr rys.	Nr pręta	Ø	Długość	Ilość	DŁUGOŚĆ ŁĄCZNA					
					RB500 W lub B500SP					
		[mm]	[mm]		Ø6	Ø8	Ø10	Ø12	Ø16	Ø20
K3	1	12	87.000	4				348,0		
	2	6	1.140	242	275,9					
	3	12	87.000	2				174,0		
	4	6	250	242	60,5					
	5	12	1.700	38				64,6		
	6	6	1.740	10	17,4					
	7	6	2.140	20	42,8					
	8	12	20.000	2				40,0		
	9	6	250	53	13,3					
K4	1	12	116.000	4				464,0		
	2	6	880	160	140,8					
	3	6	1.040	115	119,6					
	4	6	760	52	39,5					
	5	10	2.390	51			121,9			
	6	12	6.350	2				12,7		
	7	8	6.350	9		57,2				
	8	12	4.450	9				40,1		
	9	12	4.450	9				40,1		
	10	6	1.080	60	64,8					
K5	1	12	6.730	3				20,2		
	2	12	6.730	3				20,2		
	3	6	1.760	32	56,3					
K6	1	12	2.640	10				26,4		
	2	6	1.740	32	55,7					
K7	1	12	2.640	14				37,0		
	2	6	2.580	14	36,1					
	3	6	2.140	64	137,0					
Długość razem				[m]	1059,6	57,2	121,9	1287,1	0,0	0,0
Masa 1m				[kg/m]	0,222	0,395	0,617	0,89	1,58	2,47
Masa wg średnic				[kg]	235	23	75	1143	0	0
Masa razem				[kg]	1476					